

HOMEADVANTAGE
Series



Never run out of
hot water again with
***Electric Tankless
Water Heaters.***

HOMEADVANTAGE *Series*



Tank vs. Tankless



HOMEADVANTAGE *Series*



Function	Continuous heating	Hot water on-demand
Capacity	50 gallons at a time. Decreases over time due to mineral deposits.	Endless hot water. Consistent over life.
Energy Efficiency	90% - 94% efficient	99% efficient
Size	17 cubic ft < 170 lbs	1 cubic ft < 20lbs
Energy Savings \$	n/a	Up to 50%*
Avg. Life	Approx. 10 years	Up to 20 years

* when located at point of use


A never-ending supply of hot water with never-ending savings.

Eemax tankless electric water heaters activate instantly and deliver an endless supply of hot water at a preset temperature to any point of use with 99% energy efficiency.*

They're small, easy to install and service, and can last up to twice as long as traditional tank water heaters. With the new HomeAdvantage Series you get digital temperature control, "Quick Connect" water connections, advanced styling, and performance you expect.

* dependent on flow rate and incoming water temperature

Which HomeAdvantage model fits your needs?

MODEL	WARM CLIMATE GROUND WATER TEMP: 61°F-75°F	COOL CLIMATE GROUND WATER TEMP: 45°F-60°F	PRODUCT
SS012240T Max Flow 2.5 GPM	  		
SS015240TC Max Flow 3 GPM	  	 	
SS019240TC Max Flow 3 GPM	  	  	
SS023240TC Max Flow 3 GPM	    	  	
SS029240T2T Max Flow 4 GPM	    	   	
SS038240T2T2 Max Flow 6 GPM	     	    	

NUMBER OF ACTUAL
FIXTURES PER HOME



= FULL BATH



= HALF BATH



= KITCHEN

Application guide above is a representation of possible plumbing scenarios. The number of plumbing fixtures in a home running at a given time along with the type of plumbing fixture will alter the output water temperature performance.



Need help choosing the
right product?

Visit us at eemax.com or
call 800-543-6163



HOMEADVANTAGE Series

Product Line

						
Description	SS012240T HomeAdvantage	SS015240TC HomeAdvantage	SS019240TC HomeAdvantage	SS023240TC HomeAdvantage	SS029240T2T HomeAdvantage	SS038240T2T2 HomeAdvantage
Color	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Warranty						
Parts	Limited 1 year	Limited 1 year	Limited 1 year	Limited 1 year	Limited 1 year	Limited 1 year
Leaks	Limited 5 year	Limited 5 year	Limited 5 year	Limited 5 year	Limited 5 year	Limited 5 year
Unit Configuration						
No. of Chambers	1	2	2	2	3	4
Voltage	240	240	240	240	240	240
Power (KW)	11.5	15	19	23	28.5	38
Amperage	48	64	80	96	120	160
Circuits Required	1 x 50A	2 x 40A	2 x 40A	2 x 50A	3 x 40A	4 x 40A
Recommended Wire Size	1 x 6/2 AWG	2 x 8/2 AWG	2 x 8/2 AWG	2 x 6/2 AWG	3 x 8/2 AWG	4 x 8/2 AWG
Turn-on for First Stage (gpm)	0.7	0.7	0.7	0.7	0.7	0.9
Max flow (gpm)	2.5	3	3	3.5	4	6
Water Connections	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Factory Default Set Temp (Thermostatic)	140°F	140°F	140°F	140°F	140°F	140°F
Temperature Rises at 240VAC						
Temp Rise at 1.50 gpm (F)	52	68	87	105	135	100
Temp Rise at 2.00 gpm (F)	39	51	65	79	133	132
Temp Rise at 2.50 gpm (F)	31	41	52	62	76	103
Temp Rise at 3.00 gpm (F)		34	43	52	65	86
Temp Rise at 4.00 gpm (F)					49	65
Temp Rise at 5.00 gpm (F)						52
Temp Rise at 6.00 gpm (F)						43
Features						
LED Temp. Display with adjustment	Yes	Yes	Yes	Yes	Yes	Yes
Water & Electrical Connections (Top/Bottom)	Bottom	Bottom	Bottom	Bottom	Bottom	Bottom
Water Connection: "Quick Connect"	Yes	Yes	Yes	Yes	Yes	Yes

Featuring...

Digital Temperature Control:

HomeAdvantage adjusts the power applied to its heating modules to maximize energy savings by sensing inlet water temperature and flow rate.

Easy Temperature Selection:

HomeAdvantage makes it easy to adjust your exact comfort setting with finger-tip control pad and temperature LED display. Range 100°F to 140°F.

Easy "Quick Connect" Water Fittings:

Fast installation. No soldering.



Eemax, Inc.
800-543-6163
eemax.com
353 Christian Street
Oxford, CT 06478

